

## OVERVIEW

LMS engineers and manufactures commercial and military grade Fuel Quantity Indicators to exact specifications. We integrate the latest technologies in delivering devices that our customers know they can trust. The LMS Digital Indicator (square) and Analog Indicator (round) can be modified to suit any application.

## FEATURES (SQUARE)

- Analog Voltage (up to 7) or ARINC 429 (1 or 2 channels) Inputs
- Standard MS27560 Environmentally Sealed Case
- Continuous display of up to 6 tanks + total
- Error code display
- Mechanical enclosure divides the display into 4 to 7 fields
- Display Control (typically Pounds/Kilograms)
- Lighting Control Input
- Dimming Control Input
- EMI and environmentally tested as per MIL-STD-461/810 or DO-160

## FEATURES (ROUND)

- Analog Voltage (up to 4) Inputs
- Standard MS33639 2" Round Environmentally Sealed Case
- Display Control (typically Pounds/Kilograms)
- EMI and environmentally tested as per MIL-STD-461/810
- 28VDC Aircraft Power

## OPERATIONAL TEMPERATURE RANGE

- -40°C to +55°C



**DIGITAL FUEL QUANTITY INDICATOR  
(SQUARE)**



**ANALOG FUEL QUANTITY INDICATOR  
(ROUND)**

**Precise Measurement. Optimized Performance.**



**DO-160G Section and Description**
**Category**

4	Temperature & Altitude	C2
5	Temperature Variation	A
6	Humidity	B
7	Operational Shocks and Crash Safety	B
8	Vibration	S
9	Explosive Atmosphere	E
10	Waterproofness	Y
11	Fluids Susceptibility	F
12	Sand and Dust	D
13	Fungus Resistance	F
14	Salt Fog	S
15	Magnetic Effect	Y
16	Power Input	ZXX
17	Voltage Spike	A
18	Audio Frequency Conducted Susceptibility	Z
19	Induced Signal Susceptibility	ZC
20	Radio Frequency Susceptibility (Radiated and Conducted)	T
21	Emission of Radio Frequency Energy	M
22	Lightning Induced Transient Susceptibility	A4XXXX/A3J3L3
23	Lightning Direct Effects	X
24	Icing	A
25	Electrostatic Discharge (ESD)	A
26	Fire, Flammability	C